

Gaden Trout Hatchery EPA Pollution Monitoring Data.

Sampled:	05 May 2014		Monitoring Per	riod:	May, 2014				
Obtained:	10 June 2014	Licensee:		State of New South Wales (Department of Primary Industrie			Industries)		
Published	10 June 2014	EPL No.:		5035					
Sampling	Pollutant	Monitoring frequency required	No. of times measured during	Unit		Massurament	100 percentile	Exceedance	Water discharge

Sampling Point	Pollutant	Monitoring frequency required by licence	No. of times measured during month	Unit of measure	Measurement	100 percentile limit	Exceedance (yes/no)	Water discharge ML/M
1	Formaldehyde	Frequency 2	N/A	mg/L	-	0.3	-	-
	Nitrogen (total)	Monthly	N/A	mg/L	-	-	-	-
	Phosphorus (total)	Monthly	N/A	mg/L	-	-	-	-
	Total suspended solids	Monthly	N/A	mg/L	-	-	-	-
2	Nitrogen (total)	Frequency 1	Once	mg/L	-	-	-	-
	Phosphorus (total)	Frequency 1	Once	mg/L	-	_	-	-
	Total suspended solids	Frequency 1	Once	mg/L	-	-	-	-
3	Nitrogen (total)	Frequency 1	N/A	mg/L	0.3	-	-	-
	Phosphorus (total)	Frequency 1	N/A	mg/L	0.06	-	-	-
	Total suspended solids	Frequency 1	N/A	mg/L	30	-	-	-
4	Formaldehyde	Frequency 2	Once	mg/L	0.00	0.3	No	-
	Nitrogen (total)	Frequency 3	Once	mg/L	0.06	_	-	-
	Phosphorus (total)	Frequency 3	Once	mg/L	0.01	-	-	-
	Total suspended solids	Frequency 3	Once	mg/L	8.0	-	-	-



Sampling Point	Pollutant	Monitoring frequency required by licence	No. of times measured during month	Unit of measure	Measurement	100 percentile limit	Excedance (yes/no)	Water discharge ML/M
	Formaldehyde	Frequency 2	Once	mg/L	0.00	0.3	No	-
5	Nitrogen (total)	Frequency 3	Once	mg/L	0.07	-	-	-
3	Phosphorus (total)	Frequency 3	Once	mg/L	0.01	-	-	-
	Total suspended solids	Frequency 3	Once	mg/L	6.00	-	-	-

Nb. For the purpose of the above table, Frequency 1 means when a pond is drained and/or water is discharged at points 2 or 3.

For the purpose of the above table, Frequency 2 means upon commencement of discharge following treatment of ponds or raceway with formaldehyde.

For the purpose of the above table, Frequency 3 means Points 4 and 5 must be monitored whenever points 1,2 or 3 are monitored for each pollutant.